


FLS-240 pocket pal

VISUAL FAULT LOCATOR



The pocket pal is the easiest way to identify fibers from end to end and locate polished connector endfaces.

KEY FEATURES

Bright red laser at 635 nm

Pulsed and CW operation

50 hours of operation (typical)

Standard AAA alkaline batteries

Rugged and weatherproof

2.5 mm universal connector

The Pocket Pal is the easiest way to identify fibers from end to end and locate polished connector endfaces. Its red laser shines through most yellow-jacketed fibers to help you pinpoint breaks, bends, faulty connectors, splices and other causes of signal loss. It has a reach of up to 5 km*. The convenient FLS-240 locates faults visually by creating a bright red glow at the exact location of the fault on singlemode or multimode fibers.


Due to its small size, lightweight and simple but proven design, the Pocket Pal can accompany you anywhere. In your pocket or belt pouch, carry your FLS-240 to the most demanding environments. To ensure ruggedness, it features rubber seals, a fully enclosed laser head and a long-lasting On/Off switch. It has been tested to provide reliable operation under intensive use and harsh conditions.

* Typical length of continuous fiber at which end-to-end identification is possible. Visual fault location depends on ambient light conditions at test site.


SPECIFICATIONS ^a

Operation (Hz)	2 to 4
Wavelength (nm)	630 to 645
Emitter type	Laser
Power output ^b (typical) (mW)	0.8
Distance range ^c (typical) (km)	5
Operation mode	Pulsed and CW

SIX WAYS TO USE A VISUAL FAULT LOCATOR



Detects breaks in OTDR dead zone. Highlights sharp bends where losses occur. Optimizes mechanical/fusion splices.



Detects defective connectors. Ensures end-to-end fiber identification in multifiber cables. Detects major scratches on connector surfaces.

- a. Specifications are valid at 23 °C ± 1 °C.
- b. Only valid with 50/125 μm fiber.
- c. Depends on fiber attenuation.
- d. Typical battery life using AAA alkaline batteries. Battery life may fluctuate significantly, depending on specific unit's laser current.

ORDERING INFORMATION

FLS-24X-UNIV

1 = Universal 2.5 mm ferrule (CW and pulse)

Example: FLS-241-UNIV

GENERAL SPECIFICATIONS

Power supply	2 AAA alkaline batteries	
Laser class	2M	
Battery life ^d (h)	CW	35
	Pulsed	50
Length	17.5 cm (6 7/8 in)	
Maximum diameter	2.5 cm (1 in)	
Weight	Without batteries	80 g (4.8 oz)
	With batteries	120 g (6.3 oz)
Temperature	Operating	-10 °C to 50 °C (14 °F to 122 °F)
	Storage	-30 °C to 60 °C (-22 °F to 140 °F)

STANDARD ACCESSORIES

User guide, two AAA alkaline batteries, belt clip and certificate of compliance.

LASER SAFETY



Complies with 21 CFR 1040.10 except for deviations pursuant to Laser Notice No.50 dated 2007.

EXFO headquarters T +1 418 683-0211 **Toll-free** +1 800 663-3936 (USA and Canada)

EXFO serves over 2000 customers in more than 100 countries. To find your local office contact details, please go to www.EXFO.com/contact.

EXFO is certified ISO 9001 and attests to the quality of these products. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. **Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.**

For the most recent version of this spec sheet, please go to www.EXFO.com/specs.

In case of discrepancy, the web version takes precedence over any printed literature.